

Improving the Resolution of X-Ray Telescopes with Occulting Satellites

Craig J. Copi¹

cjc5@po.cwru.edu

and

Glenn D. Starkman^{1,2}

gds6@po.cwru.edu

BOSS home page: <http://boss.phys.cwru.edu/>

ABSTRACT

One of the challenges of X-ray astronomy is how to both collect large numbers of photons yet attain high angular resolution. Because X-ray telescopes utilize grazing optics, to collect more photons requires a larger acceptance angle which in turn compromises the angular resolution. All X-ray telescopes thus have angular resolution far poorer than their diffraction limit. Although collecting more photons is a desirable goal, sometimes selective collecting fewer photons may yield more information. Natural (such as lunar) occultations have long been used to study sources on small angular scales. But natural occulters are of limited utility because of their large angular velocities relative to the telescope, and because of the serendipity of their transits. We describe here how one can make use of an X-ray Big Occulting Steerable Satellite (X-BOSS) to achieve very-high resolution of X-ray sources. An X-BOSS could significantly improve the resolution of existing X-ray facilities such as the Chandra telescope, or X-ray Multiple Mirror (XMM) satellite, and could vastly improve the resolution of some future X-ray telescopes, particularly Constellation X where sub-milliarcsecond resolution is possible for a wide range of sources. Similar occulting satellites could also be deployed in conjunction with planned space observatories for other wavebands.

Subject headings: space vehicles—occultations—X-rays:general

¹Department of Physics, Case Western Reserve University, Cleveland, OH 44106-7079

²Department of Astronomy, Case Western Reserve University, Cleveland, OH 44106-7079

1. Introduction

One of the big challenges in doing X-ray astronomy is the relatively low photon fluxes from target sources. The fact that X-ray mirrors operate only at grazing angles of incidence further exacerbates this problem. Thus, while one might naively expect superb angular resolution from a 1.2 m aperture X-ray telescope such as the one on board the Chandra satellite, the 0.5 arcsecond reality is far from the 0.3 milliarcsecond nominal diffraction limit, and considerably worse than what is routinely achieved in longer wavelength bands. This situation is unlikely to change in the near future. Indeed, current plans for future X-ray missions opt for increased acceptance angle (and thus increased photon count rate) at the price of reduced angular resolution.

But it *is* possible to achieve higher X-ray photon count rates and yet improve one’s angular resolution. The necessary step is to separate the collection of photons from the means of achieving high resolution. One way to do this is well-known—occultation. When an astronomical body, such as the moon, transits the field of view of a telescope, it occults different sources within the field of view at different times. By carefully measuring the photon count rate as a function of time during the transit, one can then reconstruct the projection of the surface brightness in the field of view onto the path of the occulter.

Natural occulters *have* been used to achieve high-resolution in X-ray observations; however, they have at least two distinct disadvantages:

1. Although natural occultations can be predicted, they cannot be scheduled—target sources are therefore limited, and multiple occultations of the same source over the course of a few years are uncommon.
2. Natural occulters have large angular velocities relative to a telescope. The shorter the transit time, the fewer photons one collects, and so the lower the resolution. This is especially important for X-ray astronomy, where photon count rates are relatively low.

There is however an alternative to natural occulters which can overcome both of these disadvantages—a steerable occulting satellite. Deployment of large steerable occulting satellites has been discussed for optical and near infra-red wavebands (Adams et al. 1988; Schneider 1995; Copi & Starkman 1998, 2000), mostly for the purpose of finding planet around nearby stars, but also for high-resolution astronomical observations. However, such satellites are naturally well-suited for observations in the X-ray and far-UV. In the longer wavelength bands, minimization of diffractive losses pushes one to make the satellite as large as feasible, and deploy it as far as possible from the telescope. In the X-ray waveband one is far into the geometric optic limit and diffraction of the X-ray photons around the satellite can essentially

be neglected; thus the optimal size and placement of the satellite are determined by one's ability to accurately position the satellite with respect to the telescope-star line-of-sight and to minimize the satellite's velocity perpendicular to that line-of-sight. The resolution delivered by the combination of the X-ray telescope and the X-BOSS is determined by the collecting area of the telescope (and thus the photon count rate for a source) and by the accuracy with which one can match the X-BOSS and telescope velocity. It is independent of the intrinsic resolution of the telescope.

For an X-ray telescope either in an eccentric high-Earth orbit (Chandra and XMM) or at the L2 point of the Earth-Sun system (Constellation-X) we discuss in section 2 where to position X-BOSS relative to the satellite. In section 3 of this letter we discuss the X-ray blocking efficiency of a thick film and what it implies for the required thickness of the occulter. We also estimate in this section the required dimensions of an X-BOSS, which are determined mostly by limitations on telemetry. We discuss the steering of the X-BOSS in section 4. In section 5 we find the angular resolution that one obtains as a function of X-BOSS-telescope relative angular velocity, and of photon count rate. In section 6 we discuss the sky coverage that one could obtain in each location. Application of these techniques to specific sources is discussed briefly in section 7. Finally, section 8 contains the conclusions.

2. Locating an X-BOSS

The location of an X-BOSS is dictated by the location of the telescope it is meant to occult. The Chandra X-ray telescope is in an elliptic orbit around the Earth with an apogee of 145,417 km and a perigee of 16,026 km. The X-ray Multiple Mirror (XMM) Telescope will also be inserted into an elliptic Earth orbit. Other X-ray telescopes, such as Constellation X, may be located at the second Lagrangian point of the Earth-Sun system. The orbital issues are entirely different for these two locations; we address each in turn below. Finally, some X-ray telescopes (Astro-E and XEUS) will be placed in low earth orbit. Because orbital velocities are so high in low earth orbit, it is more difficult to make use of the approach we advocate here; we will not discuss these further.

2.1. Eccentric high Earth-orbit

As described above, the Chandra satellite is in an eccentric high altitude Earth orbit. The period of this orbit is 64 hours. The satellite therefore has an average angular velocity of about 6 arcseconds per second. An occulting satellite leading or following in Chandra's

orbit would transit a source at approximately that rate. The planned X-ray Multiple Mirror Telescope (XMM) has a similar orbit with a shorter 48 hour period. Given that the attainable angular resolution is related to the angular velocity of transit, the resolution that one could achieve with these orbits is minimal.

A great improvement is to place the X-BOSS in an orbit identical to that of the telescope but slightly modified by shifting the apogee and perigee, by changing the phase of the satellite in the orbit, or by rotating the orbit. In all cases these modifications will put X-BOSS in an orbit with the same period as telescope. In such orbits the velocity perpendicular to the line of sight of X-BOSS and the telescope can be quite low. For example, consider placing X-BOSS in an orbit identical to that of the telescope (in terms of apogee, perigee, and orbital phase) but rotated about an axis through the center of the Earth in the plane of the orbit and perpendicular to the line connecting apogee and perigee. The component of the relative velocity between X-BOSS and the telescope perpendicular to the line-of-sight between them is then zero throughout the entire orbit. Unfortunately, such an orbit intersects the telescope orbit at two points with disastrous consequences. The other orbital modifications mentioned above can alleviate this problem by enforcing a minimum separation of, for example, 10 km between the two spacecrafts. Although 10 km may seem fairly close, note that each spacecraft is only a few to tens of meters across; random errors therefore have a probability less than 10^{-9} per orbit crossing of causing catastrophic failure. The importance of utilizing these orbit modifications is explained more fully in sections 4 and 6.

2.2. Orbit at L2

We have previously discussed the orbital advantages of placing a large occulter at L2 in greater detail (Copi & Starkman 2000). Here we will highlight the important points. Orbits around L2, both in the plane of the ecliptic and oscillations perpendicular to this plane, have periods of about 6 months independent of their distance from L2 (for distances $\lesssim 10^4$ km). Therefore the local gravity is very small. Both the total velocity and acceleration of orbits around L2 (relative to the L2 point) are on par with those we might attain through carefully tuning the orbit of X-BOSS relative to that of Chandra or XMM; the relative velocity of the satellite and telescope due to the motion of L2 about the Sun is of the same magnitude. If corrections are made to the X-BOSS orbit to cancel these then the acceleration perpendicular to the line-of-sight is about $5 \times 10^{-10} \text{ m s}^{-2}$. Thus if the perpendicular velocity of X-BOSS relative to a particular line-of-sight between the telescope and some source is canceled by firing rockets, the perpendicular velocity will remain less than 10^{-4} m s^{-1} for at least a day. Tuning the velocity of X-BOSS, therefore, can be done very easily at L2.

3. Making an X-ray Occulter

3.1. Thickness

The attenuation length of X-ray photons in elemental matter is shown in figure 1. Except in hydrogen, it is approximately $3 \times 10^{-4} \text{ g cm}^{-2}$ at 1 keV, and $10^{-2} \text{ g cm}^{-2}$ at 10 keV. Thus a square 10 m on a side and one attenuation length thick has a mass of 0.3 kg at 1 keV, and 10 kg at 10 keV. At a typical density of 3 g cm^{-3} , these represent thicknesses of just 1 micron and 30 microns respectively.

A useful occulter would need to be 3–5 attenuation lengths thick, and so 3–5 microns and 1–2 kg to operate at 1 keV, and 100–150 microns and 30–50 kg to operate at 10 keV. Even at 100 keV a $10 \text{ m} \times 10 \text{ m}$ lead film 0.6 mm thick at a mass of 600 kg would provide 3 attenuation lengths of occultation.

If positioning technology improved to the point where one could reduce the size of the occulter to 1–2 m, then even gamma ray occulters would be of reasonable mass.

3.2. Size

The size of the occulting satellite depend on two factors—the aperture of the telescope and the accuracy with which one can position the occulter.

The apertures of typical X-ray satellites are about 1 m. This sets a lower bound on the dimensions of the occulter. Once the occulter is larger than the aperture of the X-ray telescope, there is essentially no effect on resolving power.

Next we will estimate how well we can determine the position of X-BOSS in the plane perpendicular to the telescope-source line-of-sight it is meant to occult. Consider a telescope separated from the X-BOSS by a distance r . We can mount a small diffraction-limited optical telescope of diameter d on the underside of the occulter. Using this telescope we can establish the relative positions of the two satellite to within approximately

$$\delta x = 1.2r \frac{\lambda}{d} = 0.5 \text{ m} \frac{r}{1000 \text{ km}} \frac{\lambda/400 \text{ nm}}{d/1 \text{ m}} \quad (1)$$

A 1 m positioning accuracy therefore requires a 50 cm finder scope at 1000 km separation, proportionately smaller at smaller separations. This is quite feasible, especially since the finder scope need not have a full UV plane.

An important question is whether one will collect enough photons to reach the diffraction limit of the angular resolution. There are two principal options—rely on reflected sunlight

or shine a laser from the X-ray telescope onto the X-BOSS telescope. Columnation is not a significant problem, as seen by our calculation of the diffraction limit above. However, sunlight has an intensity of 1000 W m^{-2} , which will be difficult to match with a laser anyway. Assuming isotropic scattering from the telescope, and a total reflecting area of 1 m^2 , this results in a flux at the X-BOSS of $3 \times 10^8 \text{ s}^{-1}$, at 1000 km (falling as $1/r^2$). Detailed studies of existing telescopes (Chandra, XMM) would be required to precisely quantify our ability to locate the telescope relative to the X-BOSS, however, these estimates suggest that determining the relative position to within 1–3 m is not unrealistic. In the case of yet-to-be launched telescopes, the mounting of a small reflector on one or more corner of the telescope would be of definite benefit.

Although we have argued that we can determine the relative position of an X-BOSS and an X-ray telescope to within about a meter, we must also be able to reduce the velocity to a fraction of a meter per second. This can be done by a simple bootstrapping procedure. Two position determinations each with error of Δx , made a time t apart, determine the velocity within $\Delta v \simeq \sqrt{2}\Delta x/t$ (assuming the error in t to be negligible). If the relative velocity can be canceled within errors by accurately firing rockets, then the ability to reduce Δv is limited by the time one can allow between position determinations, $t = \Delta x/\Delta v$. This time is limited by the orbital accelerations, but is thousands of seconds for the elliptic earth orbits of interest (cf. subsection 6.1) and hundreds of thousands of seconds for orbits at L2. (cf. subsection 6.2). In practice it may be desirable to gradually reduce the relative velocity using repeated position determinations and rocket firings.

4. Steerability

In order to successfully resolve objects it will be necessary to frequently change the velocity of the satellite. These velocity changes will occur for two principal reasons: to move from one target source to another, and to match the velocity of the X-BOSS to that of the X-ray telescope. While solar radiation pressure might be used to some advantage, it will be necessary to make some velocity adjustments using rockets. The number and size of such adjustments may be the limiting factor on the useful lifetime of the X-BOSS.

A change Δv in the satellite’s velocity is related by momentum conservation to the mass of propellant ejected, $\Delta m_{\text{propellant}}$, and the velocity of ejection v_{ejection} :

$$\Delta v_{\text{sat}} = \frac{\Delta m_{\text{propellant}} v_{\text{ejection}}}{m_{\text{sat}}}. \quad (2)$$

If N is the number of desired major rocket-driven velocity changes, then we must keep $(\Delta m_{\text{propellant}}/m_{\text{sat}}) \leq N^{-1}$. (The mass of propellant ejected will of course vary on the

particular maneuver, but here $\Delta m_{\text{propellant}}$ is taken to be some typical mass of propellant expended per orbit reconfiguration.) We therefore can accommodate only a limited number of such rocket firings:

$$N \leq \frac{v_{\text{ejection}}}{\Delta v_{\text{sat}}}. \quad (3)$$

Off-the shelf, low-cost ion engines are currently available with ejection velocities of 20 km s^{-1} , and more expensive systems with 30 km s^{-1} performance have been developed, thus

$$N \leq \frac{30 \text{ km s}^{-1}}{\Delta v_{\text{sat}}}. \quad (4)$$

Consider first the need to match the velocities of the two spacecraft so that a long occultation can occur. Δv_{sat} is then the relative velocity of the X-BOSS and the telescope in their orbits. In determining the sky coverage for elliptic Earth orbits in section 6.1 above, we have considered only orbital configurations with relative velocities between the telescope and the X-BOSS of less than 10 m s^{-1} . (Near L2, the relative velocities of relevance are typically considerably smaller than that.) If $\Delta v_{\text{sat}} \simeq 10 \text{ m s}^{-1}$, then this implies $N \leq 3000$, which is a reasonable quota of corrections for a mission with a 3–5 year lifetime, given the typical 2–3 day orbital period of Earth-orbiting X-ray telescopes.

The second type of velocity correction that will be required is target acquisition—the readjustment of the orbit of the occulter so as to allow the occultation of a new target source. For satellites separated by 1000 km near L2, relative velocities are only $v_{\text{sat}} = \mathcal{O}(10^{-4} \text{ km s}^{-1})$, and the expression for N (equation 4) shows that any constraint on target choice or order does not come from concerns about conserving propellant. For telescopes in orbit about the Earth, the matter is quite different. Here orbital velocities are $v_{\text{sat}} = \mathcal{O}(1 \text{ km s}^{-1})$, and so it is clear from the allowed number of orbital corrections (4) that one cannot indiscriminately rocket from one target to another on the sky. One solution might have been to sail in the solar radiation pressure. However, the solar radiation pressure is approximately $P_{\text{solar}} = 6 \times 10^{-6} \text{ Pa}$. For an areal density of just $1.5 \times 10^{-3} \text{ g cm}^{-2}$ (five attenuation lengths at 1 keV), this results in an acceleration of only $4 \times 10^{-4} \text{ m s}^{-2}$. At this rate it takes about a month to change velocity by 1 km s^{-1} .

Clearly one cannot reposition randomly on the sky. However the velocity difference between two orbits which result in occultation of target sources one degree apart are only of order 15 m s^{-1} . Solar sailing can cause velocity changes of this order in under a day. Moreover, the allowed number of orbital corrections (4) indicates that rocket driven corrections of this magnitude can be made of order 1000 times. How many corrections we can make, and how many sources we can therefore target for occultation, clearly depends on exactly how we use the satellite. A reasonable program of observations certainly seems possible.

5. Resolution

When used in conjunction with an X-BOSS the telescope acts as a light bucket. The angular resolution of the telescope itself is irrelevant; instead the collecting area is the important telescope parameter. The angular resolution of the system will come from probing the lightcurve as X-BOSS transits a source.

To study the angular resolution of X-BOSS we consider the simple case of identifying a binary source. Let $f(\vec{x}, t)$ be the normalized lightcurve (number of photons detected per second) generated as X-BOSS scans across a single source at a position $\vec{x}$ in the plane of X-BOSS. The lightcurve is the number of photons detected as a function of time. It is normalized such that the value is one (in the detector) when X-BOSS is not present. Since X-rays have extremely short wavelengths we can approximate the diffraction pattern produced by the satellite simply by the geometric shadow projected on the telescope. This reduces the lightcurve to a calculation of the area of the telescope not under the shadow of the occulter. We write the lightcurve of a single source as

$$l_1(\vec{x}, t) = I_1 f(\vec{x}, t) \quad (5)$$

and the total lightcurve for two sources at $\vec{x}_1$ and $\vec{x}_2$ can be written as

$$l_2(\vec{x}_1, \vec{x}_2, t) = I_2 [\rho f(\vec{x}_1, t) + (1 - \rho) f(\vec{x}_2, t)]. \quad (6)$$

Here I_i is the total intensity of the system for $i = 1$ or 2 sources and ρ is the intensity ratio of the two sources. We would like to find the minimum separation of two sources that can be distinguished from a single source. An observation consists of a sequence $\{O_j(\vec{x})/j = 1, \dots, n\}$ of measurements of the integrated lightcurve between times t_{j-1} and t_j :

$$O_j(\vec{x}) = \int_{t_{j-1}}^{t_j} dt l_i(\vec{x}, t). \quad (7)$$

To obtain limits on the minimum separation we first evaluate the number of photons expected between time t_0 and t_k

$$L_{i,k}(\vec{x}) \equiv \int_{t_0}^{t_k} dt l_i(\vec{x}, t) = \sum_{j=1}^k O_j(\vec{x}) \quad (8)$$

where i is 1 or 2 as above. Assuming the counts in each time bin, $[t_{j-1}, t_j)$, are Poisson distributed the likelihood of a model with i sources given an underlying model with 2 sources is

$$\mathcal{L}_i = \prod_{k=1}^N e^{-L_{i,k}} (L_{i,k})^{L_{2,k}} / (L_{2,k})!. \quad (9)$$

Finally the quantity

$$T = -2 \log \left(\frac{\mathcal{L}_1}{\mathcal{L}_2} \right) \quad (10)$$

is χ^2 distributed with 4 degrees of freedom (t_0 , $x_2 - x_1$, I , and ρ) and allows us to calculate the probability of misidentifying a binary source as a single source. This probability depends on $\mu_\perp$, the angular velocity of X-BOSS as it transits the source. The results for the 95% confidence limits as a function of the intensity in a 1.2 m aperture telescope for $\rho = 1$, $1/3$, and $1/10$ and for $\mu_\perp = 10 \text{ mas s}^{-1}$, $\mu_\perp = 1 \text{ mas s}^{-1}$, and 0.1 mas s^{-1} are shown in figure 2. In producing figure 2 we assumed a uniform response over the surface of the telescope. A more complicated response function may improve resolution slightly.

The simple analysis employed here uses the edges of X-BOSS in a single occultation. In practice it would be necessary to obtain multiple projections to resolve a source in two dimensions. This could be facilitated by putting slits at various angles in X-BOSS that allow for sources to be occulted by different regions of the satellite in different ways during a single transit.

6. Sky Coverage

The issues of resolution and sky coverage are closely related. Here sky coverage is the fraction of the sky for which a particular angular resolution can be obtained. While one can reposition X-BOSS to be in an arbitrary direction on the sky relative to the X-ray telescope, this frequently leads to large relative velocities and accelerations between the occulter and telescope perpendicular to the line-of-sight, thus leading to poor resolution (see figure 2). Conversely, extremely good resolution is possible if the relative velocity during the occultation is kept quite low; however this requires either special orbits (and thus very little sky coverage) or expenditures of fuel. Here we will explore the sky coverage that can be obtained subject to a number of constraints.

6.1. Elliptic Earth Orbits

We consider placing an X-BOSS in orbit around the Earth with nearly the same orbital parameters as an X-ray telescope. As discussed in section 2.1 we then allow for small alterations in the X-BOSS orbit which change the direction of the line-of-sight from the telescope to X-BOSS while keeping the X-BOSS period fixed. Our first constraint is that the minimum separation of the X-BOSS and telescope in their orbits must be larger than 10 km. (If this safety factor can be reduced then greater sky coverage may be possible.) We

then follow the two spacecrafts in their orbits to see what sky coverage these orbits afford. To limit the expenditure of propellant we consider making observations only when the relative velocity of the two satellites perpendicular to the line-of-sight is sufficiently small, here we require $v_{\perp}^{\text{orb}} < 10 \text{ m s}^{-1}$ (see section 4). Prior to an observation this velocity can be reduced to the desired range by firing the X-BOSS rockets (a small correction requiring acceptable use of consumables).

After maneuvering to correct the perpendicular relative velocity between the telescope and X-BOSS, they would still be accelerating relative to each other during the observation. This provides one limit on the total transit time of the observation. There would also be some residual error in the velocity correction, leaving X-BOSS with a component of its velocity perpendicular to the line-of-sight. This provides another limit on the total transit time of the observation. Combining these two, the total transit time over which the observation can be made is

$$t_{\text{obs}} = \min \left(\sqrt{\frac{2w}{a_{\perp}^{\text{orb}}}}, \frac{w}{\mu_{\perp}^{\text{max}} d} \right). \quad (11)$$

Here $a_{\perp}^{\text{orb}}$ is the perpendicular linear acceleration, w is the width of X-BOSS, d is the distance between the two spacecrafts, and $\mu_{\perp}^{\text{max}}$ is the maximum angular velocity allowed to obtain a particular resolution. If we require that the angular velocity perpendicular to the line of sight at the end of the observation be less than the same maximum value, $\mu_{\perp}^{\text{max}}$, then we obtain the constraint

$$a_{\perp}^{\text{orb}} t_{\text{obs}} < \mu_{\perp}^{\text{max}} d. \quad (12)$$

Of course when we cancel $v_{\perp}^{\text{orb}}$ before the observation we are also making a small change to the orbit. This leads to an extra acceleration that must also be small. If we require that this acceleration also not produce a large final velocity we obtain the constraint

$$\frac{v_{\perp}^{\text{orb}} t_{\text{obs}}^2}{r^3 d} < \frac{\mu_{\perp}^{\text{max}}}{2gR_{\oplus}^2}, \quad (13)$$

where r is the distance from X-BOSS to the (center of the) Earth, $g = 9.8 \text{ m s}^{-2}$, and $R_{\oplus}$ is the radius of the Earth.

The sky coverage on each change of X-BOSS orbit is not large. To increase the amount of sky accessible to observation we consider moving X-BOSS between orbits that are similar to the orbit of the X-ray telescope. Throughout we will consider modifications of the X-BOSS orbit that leave the period unchanged. Over many orbits this is a desired feature since it prevents the times at which X-BOSS and the telescope achieve apogee and perigee from drifting apart, requiring a large expenditure of fuel to correct. The orbital modifications we consider are increasing or decreasing the apogee distance (while preserving the semi-major

axis and thus the period), rotating the orbit about all three axes, and introducing a phase shift (time of apogee) into the orbit. For this study we taken the X-ray telescope to be the Chandra satellite and allowed changes in apogee (and perigee) of ± 200 km, rotations about the two axes in the plane of the orbit of $\pm 1^\circ$, rotations in the plane of the orbit of $\pm 0.4^\circ$, and time shifts of ± 100 s. All of these changes are relative to Chandra’s orbit. These changes can be accomplished using ion engines several thousand times before exhausting the supply of expendables (see section 4). Since occultations are best done near apogee and 1000 or so orbital periods is the Chandra mission lifetime, this rate of consumption of expendable is acceptable.

Using Monte Carlo techniques, we studied the orbits in this region of parameter space subject to two constraints: the minimum separation of the X-BOSS and telescope must be at least 10 km, and somewhere in the orbit the perpendicular velocity must be less than 10 m s^{-1} . We generated 100,000 orbits that satisfy these criteria. Next, for a variety of photon count rates and desired resolutions we used the resolution results show in figure (2) to determine $\mu_\perp^{\text{max}}$. Finally we checked which lines-of-sight satisfied the velocity and acceleration constraints (12, 13) and thus which parts of the sky can be observed. The results are shown in figure 3 assuming the width of X-BOSS is 10 m. Here even for very intense sources ($I=10^5 \text{ s}^{-1}$) only 20% of the sky can be covered with a a resolution of $\Delta\theta = 0.1$ arcsecond. This tight constraint is due principally to the fact that X-BOSS is accelerating during the time that both of the sources are occulted leading to a large velocity by the end of the observation which occurs when the transit is complete. To counteract this we could use a narrower satellite, use a satellite with slits in it so that we do not have to wait until the far edge starts unoccluding the sources, or fire the rockets while both sources are occulted to cancel the velocity. To model these possibilities we have considered a satellite that accelerates over only 2 m between the onset and end of a transit. The results are shown in figure 3b. Here we see a tremendous improvement in sky coverage and resolution. For intense sources, $I = 10^5 \text{ s}^{-1}$, we can obtain $\Delta\theta = 0.1$ arcsecond over 40% of the sky and $\Delta\theta = 0.02$ arcsecond over 20% of the sky. Larger sky coverages would be obtained if we relaxed the criteria on the orbital velocity difference between the Chandra and X-BOSS orbits. This would be justified if the propellant velocities of ion engines rose about 30 km s^{-1} , or if we could make do with a smaller number of orbital corrections.

6.2. L2 Orbits

As discussed above (section 2.2) the orbits at L2 are much simpler to manage than orbits around the Earth. Full sky coverage can be obtained and the velocity perpendicular

to the line-of-sight can be chosen as desired. Figure 2 best represents what can be achieved at L2. Since the perpendicular velocity can be chosen, extremely high angular resolution is possible. Even sub-milliarcsecond resolution is possible for many sources ($I \gtrsim 4 \times 10^3 \text{ s}^{-1}$) when $\mu_{\perp} = 0.1 \text{ mas s}^{-1}$.

7. Results

This is an exciting time for X-ray astronomy. Two new X-ray telescopes (the Chandra Advanced X-ray Astronomical Facility, and the X-ray Multiple Mirror telescope (XMM)) have been successfully launched, while another (Astro-E) is being readied for launch. Of these three, Chandra and XMM are in highly elliptical high altitude earth orbits (cf. Table 1) while Astro-E is headed for a circular low earth orbit. In addition, at least two major X-ray space-observatories are being planned: Constellation X, with launch scheduled for 2003, and XEUS with a target date of 2007. Constellation X will be placed at the L2 point of the Earth-Sun system, while XEUS, like Astro-E, will be placed in low Earth orbit.

While this may seem a remarkable proliferation of X-ray telescopes, each mission has its own emphasis. In building an X-ray telescope there is a direct competition between large effective area (and thus sensitivity) and small acceptance angle (and thus high angular resolution). Therefore one must choose whether to build an instrument which aims for high angular-resolution or one which has a goal of achieving high sensitivity. Chandra is the only high angular resolution instrument of the listed missions, with a maximum resolution of 0.5 arcsecond and thus has the relatively small effective area given above (14). The other instruments all aim for large effective area, and so sacrifice angular resolution. XMM, which is already flying, has considerably larger effective area than Chandra (and thus much lower angular resolution). Astro-E will have even larger effective area. Constellation-X will consist of multiple X-ray telescopes flown in formation, with a total effective area considerably greater than either XMM or Astro-E; it too has relatively low angular resolution compared to Chandra. Finally XEUS will have a huge effective area, and will be designed to be expandable. Its angular resolution is better than XMM, Astro-E, or Constellation-X but still not as good as Chandra. The properties of the existing and planned telescopes are shown in Table 1.

Throughout we have considered the photon rate in the detector, not at the surface of the telescope. An X-ray telescope has an effective area, $\mathcal{A}$, which includes the geometric collecting area (since grazing optics are used the collecting area is not the full beam) and the efficiency of the X-ray detector. As an example, with Chandra

$$\mathcal{A}_{\text{Chandra}} \approx 700 \text{ cm}^2 \tag{14}$$

for $E \approx 1$ keV. This is the area to be used as the area of the telescope, not the geometric area as in the case of optical telescopes. The effective area for existing and planned X-ray telescopes is given in Table 1.

The luminosity of X-ray sources varies greatly. Black holes in the cores of nearby galaxies have

$$\mathcal{L}_{\text{bh}} \approx 10^{38-40} \text{ erg s}^{-1} = 6.2 \times 10^{46-48} \text{ keV s}^{-1} \quad (15)$$

in the 0.2–2.4 keV energy range. This leads to a photon rate at the surface of the detector of

$$\Gamma_{\text{bh}} = (0.052\text{--}5.2) \times 10^{-2} \left(\frac{E}{\text{keV}} \right) \left(\frac{d}{1 \text{ Mpc}} \right)^{-2} \left(\frac{\mathcal{A}}{\text{cm}^2} \right) \text{ s}^{-1}, \quad (16)$$

where the energy, E , we observe at is given in keV and $\mathcal{A}$ is the effective area of the X-ray telescope as discussed above.

An active galactic nucleus (AGN), Seyfert galaxy, or the core of X-ray clusters can be much more luminous

$$\mathcal{L}_{\text{AGN}} \approx 10^{40-44} \text{ erg s}^{-1} = 6.2 \times 10^{48-52} \text{ keV s}^{-1}. \quad (17)$$

However, since they are approximately 100 Mpc away the photon rate is only

$$\Gamma_{\text{AGN}} = 5.2 \times (10^{-6}\text{--}10^{-2}) \left(\frac{E}{\text{keV}} \right) \left(\frac{d}{100 \text{ Mpc}} \right)^{-2} \left(\frac{\mathcal{A}}{\text{cm}^2} \right) \text{ s}^{-1}. \quad (18)$$

Galactic microquasars are somewhat less luminous

$$\mathcal{L}_{\text{microquasar}} \approx 10^{39} \text{ erg s}^{-1} = 6.2 \times 10^{47} \text{ keV s}^{-1}, \quad (19)$$

since they are in our own galaxy, though, the photon rate is fairly high

$$\Gamma_{\text{microquasar}} = 52 \left(\frac{E}{\text{keV}} \right) \left(\frac{d}{10 \text{ kpc}} \right)^{-2} \left(\frac{\mathcal{A}}{\text{cm}^2} \right) \text{ s}^{-1}. \quad (20)$$

For a 10 m X-BOSS employed in conjunction with Chandra we find (figure 3a) that for the brightest sources (galactic microquasars) we can obtain $\Delta\theta = 0.5$ arcsecond over about 30% of the sky with the sky coverage falling quickly until at $\Delta\theta = 0.1$ arcsecond very little of the sky is accessible. This represents a modest gain over what can be obtained by Chandra without the aid of X-BOSS. For a 2 m X-BOSS (figure 3b) the situation is much better. Here $\Delta\theta = 0.5$ arcsecond can be obtained over about 50% of the sky, $\Delta\theta = 0.1$ arcsecond over about 20% of the sky, and $\Delta\theta = 0.05$ arcsecond over about 5% of the sky. Thus significant improvements are attainable through the use of an X-BOSS with Chandra.

For an X-BOSS employed in conjunction with XMM the situation is similar. Although XMM has a shorter period than Chandra its has an effective area about 3 times larger (Table 1). For a 10 m X-BOSS (figure 4a) the skycoverage that can be obtained for each incident photon rate, Γ , is less than can be obtained by Chandra (compare to figure 3a) even with the factor of 3 increase in effective area that XMM provides. For a 2 m X-BOSS (figure 4b) the sky coverage for XMM and Chandra are closer though Chandra is still superior. Note that for both sizes of X-BOSS tremendous improvements over the nominal 15 arcsecond resolution for XMM are obtained.

At L2 the situation is even better. Since we can tune the velocity relative to the line-of-sight more easily, great improvements in resolution are readily available (figure 2). Sub-milliarcsecond resolution can be obtained for sources with photon rates $\Gamma \gtrsim 1000 \text{ s}^{-1}$. For a single Constellation X modules, which will have an effective area of about $15,000 \text{ cm}^2$, the brightest AGN’s, X-ray cluster cores, and galactic black holes will have $\Gamma \approx 800 \text{ s}^{-1}$ we can obtain $\Delta\theta \approx 2 \text{ mas}$.

8. Conclusions

We have found that an X-BOSS used in conjunction with an X-ray telescope can lead to tremendous improvements in angular resolution. The trend of increasing the effective area of future X-ray telescopes at the expense of angular resolution (Table 1) meshes perfectly with the benefits gained by including an X-BOSS in the mission. Indeed, an X-ray telescope to be used with an X-BOSS is treated as a light bucket with all the resolving power coming from the X-BOSS occulting the source. Thus an X-BOSS is an excellent addition to an X-ray telescope mission, particularly one at L2, such as Constellation X where sub-milliarcsecond resolution can be attained for a wide range of sources.

For the Chandra X-ray telescope we found that moderate improvements in angular resolution over an appreciable fraction of the sky can be achieved through the use of an X-BOSS. Similarly an X-BOSS employed in conjunction with XMM would provide tremendous improvements in the angular resolution that XMM could achieve allowing XMM to have angular resolution comparable to Chandra. An X-BOSS launched for use with Chandra or XMM would also provide an important test bed for the technology to be used with future missions.

The authors would like particularly to thank Art Chmielewski for financial and other support, A. Babul and M. Dragovan for many useful comments and suggestions, N. Choudhuri for helpful suggestions on statistical tests, and Paul Gorenstein and William Zhang

for comments on a preliminary version of the manuscript. This work was supported by a CAREER grant to GDS from the National Science Foundation, a DOE grant to the theoretical particle and astrophysics group at CWRU, by a grant from NASA’s Jet Propulsion Laboratory, and by funds from CWRU.

REFERENCES

- Adams, D.J. et al. 1988, ApJ, 327, L65
- Copi, C.J. & Starkman, G.D. 1998, Proceedings of SPIE, 3356, March 25, 1998, Kona, HI
- Copi, C.J. & Starkman, G.D. 2000, ApJ, 534, too appear
- Schneider, J. 1995, Proceeding of the workshop “Detection and Study of Terrestrial Extrasolar Planets”, May 15–17, Boulder, CO

Table 1. Properties of existing and planned X-ray telescopes.

Satellite Name	Effective Area at 1 keV (cm ²)	Angular Resolution (arcsecond)	Orbit
Chandra (AXAF) ^a	700	0.5	eccentric high Earth orbit
XMM	2,000	15	eccentric high Earth orbit
Astro-E	1,200	90	low Earth orbit
HETE-II ^b	350	660	low Earth orbit
Constellation X	30,000 ^c	15	L2 halo orbit
Xeus – Phase I	60,000	2	low Earth orbit
– Phase II	300,000	2	low Earth orbit

^aEffective area is for the AXAF CCD Imaging Spectrometer (ACIS). Angular resolution is for the High Resolution Camera (HRC).

^bThese values are for the wide field X-ray monitor (WXM) instrument. The quoted effective area is for 2 keV X-rays.

^cTotal effective area for all modules.

References. —

Chandra: <http://asc.harvard.edu/>

XMM: <http://xmm.vilspa.esa.es/>

HETE-II: <http://space.mit.edu/HETE/>

Astro-E: <http://heasarc.gsfc.nasa.gov/docs/astroe/overview.html>

Constellation X: <http://constellation.gsfc.nasa.gov/>

Xeus: <http://astro.estec.esa.nl/SA-general/Projects/XEUS/web/mission.html>




Fig. 1.— The photon mass attenuation length $\lambda = 1/(\mu/\rho)$ for various elemental absorbers as a function of photon energy (ρ is the density). The figure is obtained from the particle data book, figure 23.11 (<http://pdg.lbl.gov>). The data for $30\text{eV} < E < 1\text{keV}$ are obtained from http://www-cxro.lbl.gov/optical_constants (courtesy of Eric M. Gullikson, LBNL). The data for $1\text{keV} < E < 100\text{GeV}$ are from <http://physics.nist.gov/PhysRefData>, thru the courtesy of John H. Hubbel (NIST).




Fig. 2.— The minimum angular separation of two X-ray sources resolvable at the 95% confidence level. The limits are shown for intensity ratios, $\rho = 1$ (solid), $1/3$ (dashed), and $1/10$ (dashed-dotted). The upper set of three curves are for $\mu_{\perp} = 10 \text{ mas s}^{-1}$, the middle set of three curves are for $\mu_{\perp} = 1 \text{ mas s}^{-1}$, and the lower set of three curves are for $\mu_{\perp} = 0.1 \text{ mas s}^{-1}$. Note that the total photon rate is of photons detected in the telescope (without the presence X-BOSS), not photons incident on the telescope. Here d is the distance between the telescope and X-BOSS in units of 10^3 km .




Fig. 3.— The fraction of the sky that can be observed as a function of the desired resolution, $\Delta\theta$, and the photon rate in the detector (as in figure 2), Γ , for an X-BOSS used in conjunction with Chandra. (a) A satellite width of 10 m is assumed here. (b) A satellite width of 2 m is assumed here. A larger satellite can obtain these results if velocity corrections are made during the observation. See the text for details.




Fig. 4.— The same as figure 3 for an X-BOSS used in conjunction with XMM.